

## P.S. FILM

**Cad Cut® material**

<b>Description</b>	<p><b>PVC free</b> material for Cad Cut® applications. Much thinner than standard VIDEOFLEX, also has the other successful characteristics: high washing resistance, easy cutting, weeding and application. Because of its thinness, excellent performance can be achieved with multi-layered applications.</p> <p><b>Adhesive</b> Polyester backing. Suitable for 100% cotton, 100% polyester, poly-cotton blends and most synthetic fabrics</p>
<b>Tips</b>	<p><b>Custom colours on request – Minimum quantity 300 m. (450 sqm.)</b></p> <p>We highly recommend application and washing test</p>
<b>Application instructions</b>	<ol style="list-style-type: none"> <li>1)Cut in REVERSE</li> <li>2)Weed</li> <li>3)Heat apply</li> <li>4)Remove polyester backing <b>hot</b></li> </ol> <p>Due to the many different base materials available on the market, the following heat transfer instructions are given as guideline only:</p>
<b>Temperature:</b>	150°C
<b>Time:</b>	10 – 15 sec.
<b>Pressure:</b>	low
<b>Washable to:</b>	80°C Max.

### SIZES AND COLOURS

<b>ROLLS</b>	width 1,50 m.	length 25 m.
	width 0,50 m.	length 25 m.
<b>COLOURS</b>	white, cream, lemon, yellow, sun, orange, red, pink, green, dark green, sky blue, turquoise, royal blue, navy blue, violet, burgundy, brown, grey, black, gold, silver	
<b>FLUORESCENT</b>	yellow, orange, green, blue, pink, raspberry	

*Last updating: March 2007*